



**Specifications Multipack 4x Philips LED Downlight Coreline DN142B Aluminium White 19.2W 2300lm 60D - 840 Cool White | Cutout 200mm - IP20 - UGR<19.2**

[View Product](#)

## General Information

|                          |   |
|--------------------------|---|
| SKU                      | 257452                                  |
| EAN                      | 8719157070713                           |
| Brand                    | Philips                                 |
| Manufacturer Name        | Multipack 4x DN142B 20S/840 PSU-E UGR19 |
| Any Lamp all-in warranty | 5 Years                                 |
| Average Lifetime (h)     | 50000                                   |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |
| Beam Angle (degree)         | 60                |
| Luminous Efficacy (lm/W)    | 120               |

|                       |                                |
|-----------------------|--------------------------------|
| Power factor          | >0.95                          |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PC (Polycarbonate)             |
| Product Type Category | LED Downlight                  |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 200                           |
| IP-rating              | IP20                          |
| Impact Protection (IK) | IK02 - 0.20 joule             |
| Operating Temperature  | -20 to +40                    |
| Housing                | Aluminium                     |
| Colour of the Fixture  | White                         |
| Fixture Connection     | PI [Push-in connector 4-pole] |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 105 |
| Diameter (mm) | 216 |

## Sensor Information

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|

## Why Any-lamp?

 Order from the **largest lighting specialist** in Europe  **Customised** quotation

 Up to **7 years warranty**  **Easy** return process